



- ✕ escape route sign (maintained)
- ▬ bulkhead (maintained)
- bulkhead (non-maintained)
- houselight
- working light (white)
- working light (blue)

- 575W/650W Profile wide angle zoom
- 650W Fresnel
- 1kW Fresnel
- 2kW Fresnel
- Source Par MFL 575W
- Source Par WFL 575W
- Par 64 CP62 1kW
- \* re-focusable and re-gellable lantern
- § re-gellable lantern – shutters may be adjusted
- ¶ re-gellable lantern
- 203 gel number (Lee Filters/Rosco E-Colour)
- #367 gel number (Roscolux/Rosco Supergel)

- key
- scaffolding upright
  - scaffolding at grid height
  - scaffolding waist and knee rails
  - solid panel to 790mm
  - black drape
  - openable black drape on track
  - FOH display board/partition
  - internal poster wall/drape
  - limit of playing area
  - no scenic pieces downstage of this line
  - seats

- rostra/steps/steeldeck heights
- steeldeck/step @ 180mm
  - steeldeck/step @ 360mm
  - steeldeck/step @ 540mm
  - steeldeck/step @ 720mm
  - steeldeck/step @ 900mm
  - steeldeck/step @ 1080mm

Stage area approx 6m D x 6m W  
 Stage headroom approx 2.8m

C venues ltd accepts no liability for any inaccuracies  
 This plan is provisional and subject to change

For further information please contact C venues on  
 +44 (0)131 581 5520 or email production@cvenues.com

Copyright © C venues ltd – plan updated 6 July 2018