



- escape route sign (maintained)
- bulkhead (maintained)
- bulkhead (non-maintained)
- houselight
- working light (white)
- working light (blue)

lighting

key

- scaffolding upright
- scaffolding at grid height
- scaffolding waist and knee rails
- solid panel to 790mm
- black drape
- openable black drape on track
- FOH display board/partition
- internal poster wall/drape
- limit of playing area
- no scenic pieces downstage of this line
- seats (fixed)
- seats (can be removed by arrangement)

rostra/steps/steeldeck heights

- steeldeck/step @ 180mm
- steeldeck/step @ 360mm
- steeldeck/step @ 540mm
- steeldeck/step @ 720mm
- steeldeck/step @ 900mm
- steeldeck/step @ 1080mm

- 575W/650W Profile wide angle zoom
- 650W Fresnel
- 1kW Fresnel
- 2kW Fresnel
- Source Par MFL 575W
- Source Par WFL 575W
- Par 64 CP62 1kW
- \* re-focusable and re-gellable lantern
- § re-gellable lantern – shutters may be adjusted
- ¶ re-gellable lantern or over-rigged lantern
- 203 gel number (Lee Filters/Rosco E-Colour)
- #367 gel number (Roscolux/Rosco Supergel)

Stage area approx 4.7m / 5.5m / 6.3m D (dependent on seating) x 7.3m W  
 Stage headroom approx 2.3 to 2.6m (ceiling 3.1 to 3.4m)

C venues Ltd accepts no liability for any inaccuracies  
 This plan is provisional and subject to change

For further information please contact C venues on  
 +44 (0)131 581 5520 or email production@cvenues.com

Copyright © C venues Ltd – plan updated 6 July 2018