



- escape route sign (maintained)
- bulkhead or downlight (maintained)
- bulkhead (non-maintained)
- houselight
- working light (white)
- working light (blue)

lighting

- 575W/650W Profile wide angle zoom
- 650W Fresnel
- 1kW Fresnel
- 2kW Fresnel
- Source Par MFL 575W
- Source Par WFL 575W
- Par 64 CP62 1kW
- * re-focusable and re-gellable lantern
- § re-gellable lantern – shutters may be adjusted
- ¶ re-gellable lantern
- 203 gel number (Lee Filters/Rosco E-Colour)
- #367 gel number (Roscolux/Rosco Supergel)

key

- scaffolding upright
- scaffolding at grid height
- scaffolding waist and knee rails
- solid panel to 790mm
- black drape
- openable black drape on track
- FOH display board/partition
- internal poster wall/drape
- limit of playing area
- no scenic pieces downstage of this line
- seats (fixed)
- seats (can be removed by arrangement)

rostra/steeldeck heights

- steeldeck/step @ 360mm
 - steeldeck/step @ 720mm
 - steeldeck/step @ 1080mm
 - steeldeck/step @ 1440mm
 - steeldeck/step @ 1800mm
 - steeldeck/step @ 2160mm
- (intermediate steps every 180mm)

Stage area approx 4.7m / 5.5m / 6.3m D (dependent on seating) x 9m W
 Stage headroom approx 3.6m (ceiling 4.4m)

C venues ltd accepts no liability for any inaccuracies
 This plan is provisional and subject to change

For further information please contact C venues on
 +44 (0)131 581 5500 or email production@cvenues.com

Copyright © C venues ltd – plan updated 6 July 2018