



End-on Format

Stage 4.8m W x 3.5m / 2.65m / 1.8m D approx
 Stage headroom approx 2.8m to lanterns, 3.5m to grid
 Room height to ceiling 3.6m approx

Section

lighting

- Profile (MR16 12V or 300/500/575W)
- 300W Fresnel
- Source Par WFL 375W
- Birdie MR16 12V 36°
- LED Profile RGB+ 36° or similar
- LED Profile RGB+ 50° or similar
- LED Par or wash light RGB or RGB+
- re-focusable and re-gellable lantern
- gel number (Lee Filters/Rosco E-Color)
- gel number (Roscolux/Rosco Supergel)
- by arrangement, these channels can be made available for repatching

key

- escape route sign (maintained)
- bulkhead (maintained)
- bulkhead (non-maintained)
- houselight
- working light (white)
- working light (blue)
- truss
- scaffolding at grid height
- scaffolding upright
- solid barrier ground to 900mm
- black drape
- openable black drape on track
- header drape over doorway
- seats (fixed)
- seats (can be removed by arrangement)

rostra/steeldeck/step heights

- +180mm
- +360mm
- +540mm
- +720mm
- +900mm
- +1080mm
- +1260mm
- +1440mm
- +1620mm
- +1800mm

C venues Ltd accepts no liability for any inaccuracies
 This plan is provisional and subject to change

For further information please contact C venues on
 +44 (0)845 260 1030 or email production@cvenues.com

Copyright © C venues Ltd – plan updated 27 October 2017

Scale
 0 1m